

# FINISHES - FLOOR DIFFUSER AND GRILLE



# FINISHES



## LINEAR BAR GRILLE FINISHES POWDER COAT



*Standard white selection.*









*Premium white selection.*



*For field painting, color will vary.*


## ANODIZED



## OTHER FINISHES



*Available on aluminum products. Untreated from the mill, unpainted.*







*Factory washed and cleaned, unpainted.*



*Brushed aluminum with clear coat. Optional on AS, JS, SDS, LBP, LBPH, LBMH, AD3, LE.*












*Custom colors and simulated anodized finishes can be accurately matched to supplied color samples.*



**NOTE:** The colors reproduced on this Paint Finish Chart have been reproduced as accurately as possible within the limits of printed ink color reproduction technology. Colors on this chart may fade or discolor after exposure to sunlight or from age. Colors may appear to vary in actual use due to area, surface sheen, lighting (artificial or natural) or application. Therefore, variations in color or shade must be expected - we cannot guarantee otherwise. Please contact your local Global IFS Representative for an actual sample supplied on the material of construction specified.

# FINISHES

## LINEAR BAR WOODGRAIN FINISHING



Custom woodgrain, marble, granite and other custom finishes are available. Contact [solutions@globalifs.com](mailto:solutions@globalifs.com) for availability, pricing and lead times for in stock and special order options. Due to the nature of wood grain, both color and grain pattern(s) may differ slightly than what is shown above, and may also differ slightly from actual samples provided.

## QUALITY

Global IFS paint technology is markedly superior to the Electrodeposition (E-Coat) system used by most Air Distribution Manufacturers and provides an extremely durable finish that is resistant to scratching, corrosion, and rough handling.

System Comparison and Properties

Property	Price Powder Coat	Electrodeposition
Film Thickness	2.00 - 3.00 Mils	0.08 - 1.00 Mils
Hardness	2H	1H
Salt Spray Exposure	1,000 Hours	96 Hours
Impact Resistance	80 in.-lb.	80 in.-lb.

## POWDER COAT

- + Finishes have been tested to the latest applicable ASTM standards for durability and resistance to degradation from hospital grade cleaning solutions.
- + All finishes are colorfast (non-yellowing) and very durable.
- + Global IFS paint finish surpasses a 1000-hour salt spray test.

## ANTIMICROBIAL ADDITIVE


- + This additive can be added to any of our standard powder colors and will prevent the growth of micro-organisms on any painted surface.

# FINISHES


## ROUND FLOOR FINISHES



### POLYMER



### ALUMINUM



\_\_\_\_\_ Powder coat \_\_\_\_\_

**\*\*Custom Powder coat finishes available upon request**  
Note: Special Aluminum or Polymer finishes available upon request